# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# SELECTOR SWITCH OPERATOR 30MM T-K

Local distributor code: 393598999

9001KS88FB

EAN Code: 3389119001373

### Main

Range of product	Harmony 9001K
Product or component type	Head for selector switch
Device short name	9001K
Type of operator	stay put
Operator profile	Black long handle

# Complementary

Bezel material	Metal
Mounting diameter	30 mm
Net weight	0.172 kg
Shape of signaling unit head	Octagonal
Operator position information	4 positions
Contacts type and composition	Without contact block
Mechanical durability	500000 cycles
Product compatibility	9001KA1, mounted side 1 and 2
Device presentation	Basic element
Cap/operator or lens colour	Black
Operator profile	Long handle
Type of operator	Stay put
Size	30 mm
Cam profile	8

## **Environment**

Protective treatment	TC	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2570 °C	
Overvoltage category	Class II conforming to IEC 61140	
IP degree of protection	IP66 conforming to IEC 60529	

NEMA degree of protection	NEMA 1 NEMA 12		
	NEMA 13		
	NEMA 2		
	NEMA 3		
	NEMA 3R		
	NEMA 4		
Standards	UL 508		
	IEC 60947-5-4		
	JIS C 852		
	CSA C22.2 No 14		
	JIS C 4520		
	IEC 60947-5-1		
	IEC 60947-1		
Product certifications	UL 508		
	NEMA		
Vibration resistance	7 gn (f= 2500 Hz) conforming to IEC 60068-2-6		
Shock resistance	50 gn conforming to IEC 60068-2-27		

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.400 cm
Package 1 Width	4.600 cm
Package 1 Length	9.900 cm
Package 1 Weight	125.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.765 kg

# **Logistical informations**

Country of origin FR

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

Environmental Disclosure

Product Environmental Profile

### **Use Better**


Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d
REACh Regulation	REACh Declaration


### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### **Dimensions Drawings**

### **Dimensions**






 $\boldsymbol{e}$  panel thickness: 1 to 6 mm / 0.04 to 0.24 in.

### 9001KS88FB

### Mounting and Clearance

### **Contact Block Mounting Position**


### Top and Rear views



- (1) It is possible to mount up to 3 levels of contacts blocks (maximum of 6 contacts blocks)
- (2) Operator
- (3) Locating notch
- (4) Side 1
- (5) Side 2

### Panel Cut-Out

### Clearance



Legend plate	a min.		b min.	
	mm	in.	mm	in.
9001KN2••	57.2	2.25	44.5	1.75
9001KN3••	57.2	2.25	50.8	2.00

### **Individual Cut-outs Details**

### 2 alternatives

