



GreenPerform Highbay G5

BY698P G5 LED250/CW PSD WB LA

GreenPerform Highbay G5, 154 W, 25000 lm, 6500 K, DALI, 85°

The GreenPerform Highbay G5 continues the GreenPerform family’s enviable reputation for reliable performance. Not only does it deliver leading system efficacy and extended long-term quality, it also promises Unified Glare Rating (UGR) control with compact dimensions. GreenPerform Highbay G5 is also fully compatible with IoT software such as Interact, which is a scalable, future-proof control system. The family also has a series that supports cold room applications with 100% humidity and no condensation. All benefits than make this robust, optimized, and versatile family suitable for almost all industrial applications.

Product data


General Information		Light source color	
Number of gear units	1 unit	865 cool daylight	
Gear	-	Optic type	
Driver included	Yes	Wide beam	
Light source engine type	LED	Luminaire light beam spread	
Warranty period	5 years	85°	
Light Technical		Unified glare rating CEN	
Luminous Flux	25,000 lm	25	
Correlated Color Temperature (Nom)	6500 K	Effective projected area	
Luminous Efficacy (rated) (Nom)	162 lm/W	0 m²	
Color rendering index (CRI)	80	Operating and Electrical	
Number of light sources	1	Input Voltage	
Beam angle of light source	115 degree(s)	220 to 240 V	
		Line Frequency	
		50 or 60 Hz	
		Inrush current	
		60 A	
		Inrush time	
		0.6 ms	
		Power Consumption	
		154 W	
		Power Factor (Fraction)	
		0.95	
		Connection	
		Flying leads/wires	

GreenPerform Highbay G5

Cable	Cable 0.3 m without plug
Number of products on MCB of 16 A type B 6	
Suitable for random switching	Yes
Protection class IEC	Safety class I
Controls and Dimming	
Dimmable	DALI
Control interface	DALI
Maximum dim level	20%
Mechanical and Housing	
Housing Material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	Grey
Mounting device	Suspension set simple, standard
Optical cover finish	Clear
Overall height	126 mm
Overall diameter	393 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Optical cover type	Clear dome
Net Weight (Piece)	6.290 kg
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces

CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	35 °C
Ambient temperature range	-30 °C to 50 °C
UV	
UV-C radiation	0 W
UV-C irradiance defined at 0.2m	0 mW/m²
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.317, 0.338) SDCM<5
Power consumption tolerance	+/-10%
Product Data	
Order product name	BY698P G5 LED250/CW PSD WB LA
Full product name	BY698P G5 LED250/CW PSD WB LA
Order code	911401538145
Material Nr. (12NC)	911401538145
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing



GreenPerform Highbay G5

