



GreenPerform Highbay G5

BY698X G5 LED250/NW Connected WB LA

GreenPerform Highbay G5, 147 W, 25000 lm, 4000 K, BLE, 85°

The GreenPerform Highbay G5 continues the GreenPerform family’s enviable reputation for reliable performance. Not only does it deliver leading system efficacy and extended long-term quality, it also promises Unified Glare Rating (UGR) control with compact dimensions. GreenPerform Highbay G5 is also fully compatible with IoT software such as Interact, which is a scalable, future-proof control system. The family also has a series that supports cold room applications with 100% humidity and no condensation. All benefits than make this robust, optimized, and versatile family suitable for almost all industrial applications.

Product data


General Information		Light source color	
Number of gear units	1 unit	Optic type	Wide beam
Gear	-	Luminaire light beam spread	85°
Driver included	Yes	Unified glare rating CEN	25
Light source engine type	LED	Effective projected area	0 m²
Warranty period	5 years	Operating and Electrical	
Light Technical		Input Voltage	220 to 240 V
Luminous Flux	25,000 lm	Line Frequency	50 or 60 Hz
Correlated Color Temperature (Nom)	4000 K	Inrush current	10 A
Luminous Efficacy (rated) (Nom)	170 lm/W	Inrush time	0.85 ms
Color rendering index (CRI)	80	Power Consumption	147 W
Number of light sources	1	Power Factor (Fraction)	0.95
Beam angle of light source	115 degree(s)	Connection	Flying leads/wires

GreenPerform Highbay G5

Cable	Cable 0.3 m without plug
Number of products on MCB of 16 A type B 6	
Suitable for random switching	Yes
Protection class IEC	Safety class I
Controls and Dimming	
Dimmable	-
Control interface	BLE
Maximum dim level	3%
Mechanical and Housing	
Housing Material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	Grey
Mounting device	Suspension set simple, standard
Optical cover finish	Clear
Overall length	530 mm
Overall width	393 mm
Overall height	126 mm
Dimensions (Height x Width x Depth)	126 x 393 x 530 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK05 [0.7 J]
Optical cover type	Clear dome
Net Weight (Piece)	6.590 kg
Approval and Application	
Glow-wire test	Temperature 650 °C, duration 30 s

Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	35 °C
Ambient temperature range	-30 °C to 50 °C
UV	
UV-C radiation	0 W
UV-C irradiance defined at 0.2m	0 mW/m²
Initial Performance (IEC Compliant)	
Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.386, 0.384) SDCM<5
Power consumption tolerance	+/-10%
Product Data	
Order product name	BY698X G5 LED250/NW Connected WB LA
Full product name	BY698X G5 LED250/NW Connected WB LA
Order code	911401546745
Material Nr. (12NC)	911401546745
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1

Dimensional drawing



GreenPerform Highbay G5

