



SunStay

BRP710 LED30 CW MR S1 12V LFP AIO Solar

Integrated solar street light with Lithium Ferro Phosphate battery, solar panel and charger built into the luminaire. Pressure die cast aluminium for sturdiness and long life. Specially designed pole mounting bracket allows different tilt angles, lateral and pole top mounting.

Integrated solar street light with Lithium Ferro Phosphate battery, solar panel and charger built into the luminaire. Pressure die cast aluminium for sturdiness and long life. Specially designed pole mounting bracket allows different tilt angles, lateral and pole top mounting.

Product data

General Information	
Light source color	Cool white
Driver included	Yes
Optical cover/lens type	UV stabilized Polycarbonate cover
Operating and Electrical	
Battery type	Lithium Ferro Phosphate
Battery ampere hour	20 Ah
Battery voltage	12.8 V
Battery charging & discharging cycles	2000
Panel type	Mono crystalline
Panel voltage	17 Vmp, 21 Voc V
Panel peak wattage	35 W
Charge controller type	MPPT

Yes
Factory Configurable
Aluminium pressure die cast
684 mm
369 mm
156 mm
Gray
IP65 [Dust penetration-protected, jet-
proof]

SunStay

Initial Performance (IEC Compliant)	
Initial luminous flux (system flux)	3000 lm
Initial LED luminaire efficacy	175 lm/W
Init. Corr. Color Temperature	5700 K
Init. Color Rendering Index	>70
Initial input power	17 W

Battery location	Inside Luminaire
Product Data	
Full product code	871016335461300
Order product name	BRP710 LED30 CW MR S1 12V LFP AIO
	Solar
EAN/UPC - Product	8710163354613
Order code	919515812388
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	919515812388
Net Weight (Piece)	11.000 kg

Off grid

Grid connection type

IP 65

Median useful life L70B50	50000 h
Anniisatian Conditions	

Over Time Performance (IEC Compliant)

Application Conditions	
Ambient temperature range	0 to +35 °C
Ambient temperature range for charging	0 to +45 °C
Ambient temperature range for discharging	-20 to +35 °C
(when light is on)	
Solar dimming profile	30% Dusk to dawn, 100% on motion.
	(Sensor disabled for 5 Hrs, after 5 Hrs)



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.