# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# UTP 24-port Patch Panel, UnLoaded



ACTPP6U24NSSUN

### Main

range of product	Actassi
Product or component type	Patch panel
Device presentation	Empty
Provided equipment	Without RJ45 connectors

# Complementary

[In] rated current	1.5 A	
Number of port	24 port of UTP	
Product compatibility	standard 19" cabinet/rack	
Communication network category	6 5e	
Contact resistance	20 μOhm	
Insulation resistance	>= 10 MOhm	
Minimum number of matings	750 cycles	
Number of rack unit	1U	
Type of connector	S-110 keystone	

## **Environment**

Ambient air temperature for operation	-1050 °C
Ambient air temperature for storage	-2060 °C
Relative humidity	093 %
Standards	TIA/EIA-568-B

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	12.5 cm
Package 1 Length	49.7 cm
Package 1 Weight	816.0 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	7
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No