Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Actassi - patch panel - category 6 -UTP - 24-port - non shuttered loaded



ACTPP6U24NSS_S

Main

range of product	Actassi
Product or component type	Patch panel
Device presentation	Loaded
Provided equipment	With RJ45 connectors

Complementary

[In] rated current	1.5 A	
Number of port	24 port of UTP	
Product compatibility	standard 19" cabinet/rack	
Communication network category	6	
Contact resistance	1 mOhm	
Insulation resistance	>= 200 MOhm	
Minimum number of matings	1000 cycles	
Number of rack unit	1U	
Type of connector	S-110 keystone	

Environment

Ambient air temperature for operation	-4070 °C
Ambient air temperature for storage	-2060 °C
Relative humidity	093 %
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801 Ed.2, 2002

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.77 cm
Package 1 Width	4.34 cm
Package 1 Length	48.3 cm
Package 1 Weight	990.0 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Total lifecycle Carbon footprint	43	

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No