

APC NetShelter Rack PDU Advanced Gen 2, Metered, 7.4kW, 1Phase, 230V, 32A, 332P6, 40 **Outlets**

APDU11150ME

! Launching in: 31 October 2025

① Coming soon

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	3 m

Complementary

Input Voltage	230 V 1 phase		
Height	1490 mm		
Width	56 mm		
Output Voltage	230 V		
Depth	75 mm		
Net weight	6.2 kg		
Mounting location	Side		
Mounting preference	No preference		
Input Plug Type	IEC 60309 32 A 2P + PE		
Mounting mode	Rack-mounted		
Rack units	0U		
Mounting position	Vertical		
Communication port protocol	1000BASE-T 10/100BASE-T		
[In] rated current	32 A		
Permissible voltage	200240 V		
Input current limits	32 A		
Load capacity	7400 VA		
Network frequency	50/60 Hz		
Outlet type and quantity	20 C13/C15/C19/C21 20C13/C15		

Environment

Product certifications	UKCA
Standards	CE EN 62368-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	8.2 kg

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances			
Packaging made with recycled cardboard	No		
Packaging without single use plastic	No		
EU RoHS Directive	Compliant with Exemptions		
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da		
REACh Regulation	REACh Declaration		

Use Again

○ Repack and remanufacture		
Take-back	No	

Image of product / Alternate images

Alternative



