① Coming soon



APC NetShelter Rack PDU Advanced Gen 2, Switched, 7.4kW, 1Phase, 230V, 32A, 332P6, 40 Outlet

APDU11150SW

! Launching in: 31 October 2025

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Cord length	3 m

Complementary

Input Voltage	230 V 3 phases	
Height	1490 mm	
Width	56 mm	
Output Voltage	230 V	
Depth	75 mm	
Net weight	7.4 kg	
Mounting location	Side	
Mounting preference	No preference	
Input Plug Type	IEC 60309 32 A 2P + PE	
Mounting mode	Rack-mounted	
Rack units	OU	
Mounting position	Vertical	
Communication port protocol	1000BASE-T 10/100BASE-T	
[In] rated current	32 A	
Permissible voltage	200240 V	
Input current limits	32 A	
Load capacity	7400 VA	
Network frequency	50/60 Hz	
Outlet type and quantity	20 C13/C15/C19/C21 20C13/C15	

Environment

Product certifications	UKCA
Standards	CE EN 62368-1
Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	9.4 kg

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
Take-back	No	

Product datasheet APDU11150SW

Image of product / Alternate images

Alternative

APDU11150SW





APDU11150SW

