

APC NetShelter Rack PDU Advanced Gen 2, Metered, 5.0kW, 1Phase, 208V, 30A, L6-30P, 40 Outlet

APDU11151ME



Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	3 m

Complementary

Input Voltage	208 V 1 phase
Height	1490 mm
Width	56 mm
Output Voltage	208 V
Depth	75 mm
Net weight	6.6 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	NEMA L6-30P
Mounting mode	Rack-mounted
Rack units	OU
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
[In] rated current	24 A
Permissible voltage	200240 V
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz
Outlet type and quantity	20 C13/C15/C19/C21 20C13/C15

Environment

Standards	UL 62368-1 CSA C22.2 No 62368-1 FCC part 15 Subpart B
IP degree of protection	IP44
Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	8.6 kg

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances			
Packaging made with recycled cardboard	No		
Packaging without single use plastic	No		
EU RoHS Directive	Compliant with Exemptions		
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da		
REACh Regulation	REACh Declaration		

Use Again

○ Repack and remanufacture		
Take-back	No	

Image of product / Alternate images

Alternative



