


APDU11250ME



! Launching in: 31 October 2025

Overview

Lead time Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	3 m

Complementary

Input Voltage	415 V 3 phases 400 V 3 phases
Height	1490 mm
Width	56 mm
Output Voltage	240 V
Depth	55 mm
Net weight	5.7 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 20 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Communication port protocol	1000BASE-T 10/100BASE-T
[In] rated current	16 A
Permissible voltage	200240 V 346415 V
Input current limits	20 A
Load capacity	11500 VA
Network frequency	50/60 Hz

Outlet type and quantity	21 C13/C15/C19/C21	
	21C13/C15	

Environment

Product certifications	UKCA
Standards	UL 62368-1
	CSA C22.2 No 62368-1
	FCC part 15 Subpart B
	CE
	EN 62368-1
IP degree of protection	IP44
Ambient air temperature for operation	-560 °C
Relative humidity	595 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	595 %
Storage altitude	015240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	172 cm
Package 1 Width	11.6 cm
Package 1 Length	20.8 cm
Package 1 Weight	7.7 kg

Contractual warranty

Warranty 3 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
Take-back	No	

Image of product / Alternate images

Alternative



