

variable speed drive Altivar Lift, 15 kW 20 Hp, 380...480 V three-phase, EMC filter, with heat sink

ATV71LD33N4Z

### Main

Device short name	ATV71	
Product destination	Asynchronous motors	
	Synchronous motors	
Network number of phases	3 phases	
Supply voltage limits	323528 V	
Supply frequency	5060 Hz - 55 %	
Motor power kW	15 kW, 3 phases at 380480 V	
Motor power hp	20 hp, 3 phases at 380480 V	
Line current	48 A for 380 V 3 phases 15 kW / 20 hp	
	39 A for 480 V 3 phases 15 kW / 20 hp	
Range of product	Altivar Lift	
Product or component type	Variable speed drive	
Product specific application	Lift	
Variant	With integrated 7-segment display terminal	
Communication port protocol	Modbus	
	CANopen	
[Us] rated supply voltage	380480 V - 1510 %	
EMC filter	Integrated	

## Complementary

Apparent power	31.6 kVA at 380 V 3 phases 15 kW / 20 hp	
Prospective line Isc	22 kA for 3 phases	
Nominal output current	33 A at 4 kHz 380 V 3 phases 15 kW / 20 hp 27 A at 4 kHz 460 V 3 phases 15 kW / 20 hp	
Maximum transient current	44.9 A for 2 s 3 phases / 15 kW / 20 hp	
Speed drive output frequency	0599 Hz	
Speed range	1100 for asynchronous motor in open-loop mode, without speed feedback     150 for synchronous motor in open-loop mode, without speed feedback     11000 for asynchronous motor in closed-loop mode with encoder feedback	
Torque accuracy	+/- 5 % in closed-loop mode with encoder feedback +/- 15 % in open-loop mode, without speed feedback	
Transient overtorque	170 %, +/- 10 % for 60 s 220 %, +/- 10 % for 2 s	
Braking torque	30 % without braking resistor <= 150 % with braking or hoist resistor	
Local signalling	1 LED (red) for drive voltage	

Oppper 90 °C / XLPE/EPR Oppper 70 °C / PVC 0 °C, copper 70 °C / PVC 0 °C, copper 75 °C / PVC -/Al1+, Al2, AO1, R1A, R1B, , L2/S, L3/T, U/T1, V/T2, W/T3, //T3, PC/-, PO, PA/+, PA, PB) , R2B, Ll1Ll6, PWR)	
Opper 70 °C / PVC 1 °C, copper 70 °C / PVC 2 °C, copper 70 °C / PVC -/AI1+, AI2, AO1, R1A, R1B, 1, L2/S, L3/T, U/T1, V/T2, W/T3, -/T3, PC/-, PO, PA/+, PA, PB)	
, L2/S, L3/T, U/T1, V/T2, W/T3, /T3, PC/-, PO, PA/+, PA, PB)	
Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC +/- 5 %, <10 A, protection type: overload and short-circuit protection Internal supply: 24 V DC (2127 V), <200 A, protection type: overload and short-circuit protection	
crete input(s)	
ete output(s) tput(s)	
+/- 0.6 % (Al1-/Al1+) for a temperature variation 60 °C +/- 0.6 % (Al2) for a temperature variation 60 °C +/- 1 % (AO1) for a temperature variation 60 °C	
+/- 0.15 % of maximum value (AI1-/AI1+, AI2) +/- 0.2 % (AO1)	
AO1 software-configurable voltage: 010 V DC, impedance: 470 Ohm, resolution 10 bits AO1 software-configurable current: 020 mA, impedance: 500 Ohm, resolution 10 bits AO1 software-configurable logic output 10 V 20 A	
Configurable relay logic: (R1A, R1B, R1C) NO/NC - 100000 cycles Configurable relay logic: (R2A, R2B) NO - 100000 cycles	
5 A at 250 V AC on resistive load - cos phi = 1 - L/R = 0 ms (R1, R2) 5 A at 30 V DC on resistive load - cos phi = 1 - L/R = 0 ms (R1, R2) 2 A at 250 V AC on inductive load - cos phi = 0.4 - L/R = 7 ms (R1, R2) 2 A at 30 V DC on inductive load - cos phi = 0.4 - L/R = 7 ms (R1, R2)	
- 3500 Ohm - 3500 Ohm - 1500 Ohm	
Positive logic (LI6)if configured as logic input, < 5 V (state 0), > 11 V (state 1)  Negative logic (LI6)if configured as logic input, > 16 V (state 0), < 10 V (state 1)  Positive logic (LI1LI5), < 5 V (state 0), > 11 V (state 1)  Negative logic (LI1LI5), > 16 V (state 0), < 10 V (state 1)  Positive logic (PWR), < 2 V (state 0), > 17 V (state 1)	
3535 V DC between earth and power terminals 5092 V DC between control and power terminals	
> 1 mOhm 500 V DC for 1 minute to earth	
Display unit: 0.1 Hz Analog input: 0.024/50 Hz	
1 RJ45 (on front face) for Modbus 1 RJ45 (on terminal) for Modbus Male SUB-D 9 on RJ45 for CANopen	

Transmission frame	RTU for Modbus	
Transmission rate	9600 bps, 19200 bps for Modbus on front face 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps for Modbus on terminal 20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps for CANopen	
Data format	8 bits, 1 stop, even parity for Modbus on front face 8 bits, odd even or no configurable parity for Modbus on terminal	
Type of polarization	No impedance for Modbus	
Number of addresses	1247 for Modbus 1127 for CANopen	
control options	Communication card for Modbus TCP Communication card for Fipio Communication card for Modbus/Uni-Telway Communication card for Modbus Plus Communication card for EtherNet/IP Communication card for DeviceNet Communication card for Profibus DP Communication card for Profibus DP V1 Communication card for Interbus-S Communication card for CC-Link Interface card for encoder I/O extension card Controller inside programmable card Overhead crane card	
Discrete input number	7	
Discrete output number	2	
Analogue input number	2	
Analogue input type	Al2 software-configurable voltage: 010 V DC 24 V max, impedance: 30000 Ohm, resolution 11 bits  Al1-/Al1+ bipolar differential voltage: +/- 10 V DC 24 V max, resolution 11 bits + sign  Al2 software-configurable current: 020 mA, impedance: 242 Ohm, resolution 11 bits	
Analogue output number	1	
Method of access	Slave CANopen	
Asynchronous motor control profile	Voltage/frequency ratio - Energy Saving, quadratic U/f Flux vector control without sensor, standard Flux vector control without sensor, ENA (energy Adaptation) system Voltage/frequency ratio, 5 points Flux vector control with sensor, standard Voltage/frequency ratio, 2 points Flux vector control without sensor, 2 points	
Synchronous motor control profile	Vector control without sensor, standard     Vector control with sensor, standard	
Acceleration and deceleration ramps	S, U or customized Linear adjustable separately from 0.01 to 9000 s Automatic adaptation of ramp if braking capacity exceeded, by using resistor	
Motor slip compensation	Automatic whatever the load  Not available in voltage/frequency ratio (2 or 5 points)  Suppressable  Adjustable	
Switching frequency	116 kHz adjustable	
Nominal switching frequency	8 kHz	
Minimum braking resistance	7 Ohm	
Network frequency	47.563 Hz	

Protection type	Overheating protection: drive
	Thermal protection: drive
	Short-circuit between motor phases: drive
	Input phase breaks: drive
	Overcurrent between output phases and earth: drive
	Overvoltages on the DC bus: drive
	Break on the control circuit: drive
	Against exceeding limit speed: drive
	Line supply undervoltage: drive
	Line supply overvoltage: drive
	Against input phase loss: drive
	Thermal protection: motor
	Motor phase break: motor
	Power removal: motor

## **Environment**

Pollution degree 2 conforming to IEC 61800-5-1		
P degree of protection	IP20 on upper part without blanking plate on cover conforming to IEC 61800-5-1 IP20 on upper part without blanking plate on cover conforming to IEC 60529 IP21 conforming to IEC 61800-5-1 IP21 on upper part conforming to IEC 61800 5.1	
	IP41 on upper part conforming to IEC 61800-5-1 IP41 on upper part conforming to IEC 60529	
	IP54 on lower part conforming to IEC 60829	
	IP54 on lower part conforming to IEC 60529	
Vibration resistance	1.5 mm peak to peak (f= 313 Hz) conforming to IEC 60068-2-6 1 gn (f= 13200 Hz) conforming to IEC 60068-2-6	
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27	
Noise level	60.2 dB conforming to 86/188/EEC	
Relative humidity	595 % without condensation conforming to IEC 60068-2-3 595 % without dripping water conforming to IEC 60068-2-3	
Ambient air temperature for operation	-1050 °C (without derating)	
Operating altitude	<= 1000 m without derating 10003000 m with current derating 1 % per 100 m	
Operating position	Vertical +/- 10 degree	
Product certifications	C-Tick	
	CSA	
	GOST	
	UL NOM 117	
Marking	CE	
Standards	EN 55011 class A group 2	
	IEC 61800-3 environments 1 category C3 IEC 61800-5-1	
	IEC 61800-3-1 IEC 61800-3 environments 2 category C3	
	IEC 60721-3-3 class 3C1	
	UL Type 1	
	IEC 60721-3-3 class 3S2 IEC 61800-3	
Assembly style	With heat sink	
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3	
	Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5	
	Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-3	
	Voltage dips and interruptions immunity test conforming to IEC 61000-4-11	
Regulation loop	Adjustable PI regulator	
Speed accuracy	+/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn +/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn	
Ambient air temperature for storage	-2570 °C	

# **Packing Units**

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.000 cm
Package 1 Width	60.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	17.391 kg
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	43.282 kg

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

#### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	A8622d9d-a8bf-41fe-8724-1359349428e6
REACh Regulation	REACh Declaration
᠃ Energy efficiency	
Product contributes to saved and avoided emissions	Yes

#### **Use Again**

☼ Repack and remanufacture		
Take-back	No	