

# Product datasheet

Specifications



## Servo motor, Easy Lexium 18, 750W, M80, 23 bits, OPTO INC

BCH18MF07332A5C

### Main

Range compatibility	Easy Lexium 18
Device short name	BCH18
Product or component type	Servo motor

### Complementary

Maximum mechanical speed	6000.0 rpm
[Us] rated supply voltage	200...240 V
Continuous stall current	4.9 A
Continuous stall torque	2.39 N.m, 220 V
Continuous power	750 W
Peak stall torque	8.37 N.m, 220 V
Nominal output power	750 W, 220 V
Nominal torque	2.39 N.m, 220 V
Nominal speed	3000 rpm, 220 V
Maximum permanent current	17.3 A
Shaft end	Parallel key
Shaft diameter	19.0 mm
Shaft length	35.0 mm
key width	6.0 mm
Feedback type	23 bits optic incremental encoder
Holding brake	Without
Mounting support	Asian standard flange
Motor flange size	80 mm
Electrical connection	2 connectors male/female
Torque constant	0.49 N.m/A at 40 °C
Back emf constant	31.0 V/krpm at 40 °C
Number of motor poles	5.0
Rotor inertia	1.79 kg.cm²
Stator resistance	1.5 Ohm
Stator inductance	5.0 mH
Maximum radial force Fr	392 N

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Maximum axial force Fa	147 N
Length	113.7 mm
Number of mounting holes	4.0
Circle diameter of the mounting holes	6.5 mm
Width	113.7 mm
Height	80.0 mm
Depth	88.6 mm
Net weight	2.5 kg
Encoder type	Optic encoder

## Environment

IP degree of protection	IP67
Ambient air temperature for operation	0...40 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.8 cm
Package 1 Width	18.2 cm
Package 1 Length	28.3 cm
Package 1 Weight	2.7 kg
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	39.7 cm
Package 2 Length	59.8 cm
Package 2 Weight	21.6 kg





## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Total lifecycle Carbon footprint	7602
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant
REACH Regulation	<a href="#">REACH Declaration</a>

### Use Again

Repack and remanufacture	
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No