

Disconnecting device, EasyPact EXE, basic function, 17.5kV, 31.5kA 3s, 2500A, 275mm, IEC

EXE173125M1D

Main

mam	
Master range	Easy Series
Range of product	EasyPact
Product name	EasyPact EXE
Product or component type	Disconnecting device
Breaking technology	Vacuum
Pole type	Open
Number of poles	3
Network type	AC
Type of installation	Indoor
Integration type	Withdrawable
Variant	Basic function
Standards	IEC 62271-102:2013
Rated voltage (Ur)	17.5 kV
Rated short-duration power frequency withstand voltage (Ud) / Common value	38 kV
Rated lightning impulse withstand voltage (Up) / Common value	95 kV
Rated frequency (fr)	50/60 Hz
Rated continuous current (Ir)	2500 A
Rated short-time withstand current (lk)	31.5 kA
Rated duration of short-circuit (tk)	3 s
Rated peak withstand current (Ip)	79 kA 50 Hz 82 kA 60 Hz

Complementary

Mass	150 kg
Height	527 mm
Width	724 mm
Depth	429 mm
Phase distance	275 mm
Clearance in air to earth	140 mm
Upper lower connection distance	205 mm

Environment

Product certifications	ASEFA	
Ambient air temperature for operation	-2540 °C	
Ambient air temperature for storage	-4070 °C	
Humidity conditions	Average relative humidity over 24 h <= 95 % Average relative humidity over 1 month <= 90 %	
Operating altitude	<= 1000 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	58.7 cm
Package 1 Width	80.0 cm
Package 1 Length	60.0 cm
Package 1 Weight	55.0 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Total lifecycle Carbon footprint	764	

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	409e50bf-7b4e-47fe-83a3-6420f9386633
REACh Regulation	REACh Declaration
PVC free	No

Use Again

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No