

Modicon M171 Performance Plug-in Modbus SL

TM171AMB

Main

Range of product	Modicon M171	
Product or component type	Communication module	
Communication port protocol	Modbus RTU RS485	

Complementary

Integrated connection type	RS485 wire crimp - twisted pair
Adjustment	Pitch 3.81 mm
Electrical connection	removable screw terminal block
Physical interface	90° insertion - 2.5 mm² cable
Supply	Via base board EVD/EVC
Product compatibility	Logic controller M172 performance Logic controller M171 performance
Net weight	0.077 kg

Environment

Product certifications	EAC CSA CE cURus
Marking	CE
IP degree of protection	IP20
Ambient air temperature for operation	-1055 °C
Ambient air temperature for storage	-2085 °C
Relative humidity	1090 % without condensation

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.0 cm
Package 1 Width	9.1 cm
Package 1 Length	18.5 cm
Package 1 Weight	166.0 g
Unit Type of Package 2	S02

Number of Units in Package 2	6
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.306 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better


Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
Take-back	No	

Dimensions Drawings

Dimensions




TM171AMB


Mounting and Clearance

Mounting and Clearance


Clearance




Misplacement



Mounting on Controller



Dismounting



TM171AMB

Connections and Schema

Connections and Schema

RS 485 Communication Module

TM171AMB

